



Date Issued: 18.09.09

Supaturf Product Specification Sheet

Supamark Aerosols

	Stock codes	750ml Extra	750ml Standard
	White	02519	02521
	Yellow	02516	02518
	Red	02514	02515
	Deep Blue	02506	02507
	Green	02511	02512
	Orange	02508	02509
	Grey	02503	02510
What is it	A xylene free solvent based aerosol marking liquid		
For use on	Tarmac, Concrete, Brick, Turf, AstroTurf, Wood, Metal and Shale		
Application Rates	Neat – Direct from the can 1 x 750ml can will provide 100 metres of a 50mm width line @ 2.25mph.		
What ingredients are used in the formulation	Proprietary blend of inorganic pigment dispersion held within an aerosol can. Contains binders resins for adhesion of the product to the applied surfaces.		
Recommended for use with:	Supamarker and GUR Aerosol Applicators		
Drying time (dependant on air movement, humidity, dampness of substrate when applied)	Touch dry after 20 mins Fully cured after 24 hrs		
Application Information	Surface must be free from dust, grease and any extraneous matter before application. Do not apply where surface are damaged and in need of repair. Always shake the can for 1-2 minutes before application. Store the can on its side to prevent blocking. Avoid applying the products when windy.		
Re-coat time	24 hours		
Scrub Resistance	Good		
Durability	Good		
Image			

Contact us at: www.supaturf.co.za

Supaturf South Africa – Main dealer/Head Office/KwaZulu-Natal:

231 Lothian Road, Durban North, 4051, South Africa

Email: info@supaturf.co.za ,Tel: 0315632513, Fax: 0315635251, Cell: 0836532513

Supaturf South Africa