



Date Issued: 18.09.09

**Supaturf Product Specification Sheet**

**Supaturf Supastadia Eco**

Product Code	5 Litre		
What is it	A highly concentrated bright white water based emulsion line marking liquid		
Product Characteristics	Smooth medium density flowable emulsion based line marking liquid with good colour performance on dilution		
Colour Measurements	Whiteness Index min	88%	
	Dry Hiding Power min	98%	
Typical Physical Properties	Wear Resistance – Rating	11 – Good	
	Sedimentation Rating	5 – Excellent	
	Weight per litre	1.7kg	
	Viscosity	Medium/High	
For Use On	Turf, Red and Grey Shale, Artificial Turf		
Recommended Dilution Rates for spray marking	Initial Marking	1 part Eco to 12 parts water	
	General Marking	1 part Eco to 16 parts water	
	Over Marking	1 part Eco in up to 20 parts water	
What ingredients are used in the formulation	Proprietary blend of inorganic pigment dispersion with binder resins for adhesion of the product to the applied surface.		
Recommended for use with the Supaturf:	TXE 252 and TLS		
Drying Time (dependant on air movement, humidity, dampness of substrate when applied)	Approximate:		
	Warm 20°C and above	3 – 5 min	
	Cool 10°C to 20°C	5 – 15 min	
	Cold 1°C to 10°C	15 – 60 min	

**Contact us at: [www.supaturf.co.za](http://www.supaturf.co.za)**

**Supaturf South Africa – Main dealer/Head Office/KwaZulu-Natal:  
231 Lothian Road, Durban North, 4051, South Africa**

**Email: [info@supaturf.co.za](mailto:info@supaturf.co.za) ,Tel: 0315632513, Fax: 0315635251, Cell: 0836532513**

S P A T I F I C A T I O N S