




Date Issued: 18.09.09

Supaturf Product Specification Sheet

TXE Spray Boom

| | | |
|----------------------------------|---|--|
| Stock Code | | 02017 |
| Function | The TXE spray boom. Fits to the front of any TXE model. Converts the TXE line marking into a sprayer. |  |
| Features | <ul style="list-style-type: none"> • Easy to fit to any of the TXE machines • 1.5m spray width • Spray output 0.67 litre/minute per nozzle • Wet spray boom • Instant product spray cut off set at 10 psi | |
| Spray | Pump pressure and flow: with 3 TL brass nozzles 0.67 litre/min @ 2.2 bar. | |
| Spray Boom | When attached to the machine allows a flat fan of product to be sprayed across a width of 1.5 metres. | |
| Construction – Spray Boom | Manufactured 3/4" 10 gauge aluminium tube with 3 nozzle mount diaphragm check valves set at 10 psi with 6mm centre mount for pipe connection from pump. | |
| Mount Frame | Comprising of 2 swaged 'S' bends coupled made from 19.1 dia 1.6 gauge lacquered triple coated zinc galvanised steel tube, to provide a mount for the spray boom. The unit is plugged into the front of the machine and secured by 2 'D' clamps. The boom is positioned on the top of the 'S' bends and secured by 2 'J' bolts and hands wheels. | |
| Weights & Dimensions | Boxed length 1185mm width 240mm height 110mm Weight boxed 2.64kg Boom and 'S' bends only 1.98kg Boom only 0.7kg | |

Contact us at: www.supaturf.co.za

Supaturf South Africa – Main dealer/Head Office/KwaZulu-Natal:

231 Lothian Road, Durban North, 4051, South Africa

Email: info@supaturf.co.za ,Tel: 0315632513, Fax: 0315635251, Cell: 0836532513

SPECIALIST SUPATURF